

EUP45T-1WMC-0

Summary


EUP45T-1WMC-0 is a constant current mode output LED driver. The output current can be easily set via the DIP dial switch. The driver supports leading edge (Triac) and trailing edge (ELV) dimmer, and can be compatible with the systems of various brands (Philips, Panasonic, Lutron, Simon, ABB, Siemens etc.) to achieve a smooth dimming effect.

Product Feature

- Multi-current driver selected by Dip-switch
- Support Leading edge (Triac) and Trailing edge (ELV) Dimmer.
- Dimming range from 40VAC to 240C.
- Dimming effect smooth, no flicker
- High efficiency up to 87%
- Output short circuit protection; over current protection
- Suitable for indoor LED lighting application, down light, panel light, and so on



Application



Technical Parameters



Model	EUP45T-1WMC-0	
Input	Efficiency	87%@230VAC, Full load
	Voltage	200VAC-240VAC
	Frequency	50/60Hz
	Power Factor	>0.5@230VAC, Full load
	Current	0.4Amax@230VAC, Full load
	Dimming voltage range	40-240VAC
	Inrush Current	20A@230VAC
Output	Current/Voltage/Power	500mA/33-65VDC/32.5W 900mA/33-50VDC/45W 700mA/33-65VDC/45.5W 1050mA/33-42VDC/44.1W
	Ripple Current	<3%
	Channel	1
	Current Tolerance	±7%
	No Load Output Voltage	84V Max
	Turn On Delay Time	<1s, at 230Vac
Function	Dimming Mode	Triac ELV
	Protection	Short Circuit: Hiccups, recovers automatically after fault condition removed Over Current: Hiccups, recovers automatically after fault condition removed
Others	Working Temp.	-20°C~40°C
	Storage Temp.; Humidity	-40°C~85°C, 20-90%RH
	Tc	90°C
	Material	PC
	IP Rating	IP20
	Lifetime	30,000h@tc:90°C
	Warranty Condition	3 years
	Switch Cycle	>15,000 times
	Packing Size	Net weight: 225g±5%/PCS; 50PCS/Carton; 11.75kg±5%/Carton; Carton Size: 516*337*179cm[L*W*H]
Dimension	137*82*31mm[L*W*H]	

Current Selection Table


ON	OFF	1	2	3	4	5	6	7	8	9	10
		500mA	700mA	900mA	1050mA						
		33-65V	33-65V	33-50V	33-42V						

Remark: Function default setting is: 500mA (@switch are all OFF state)


Dimension(mm)




Wiring Diagram




Dimming Curve



Derating Curve



Eff. vs Load



Cautions

- 1.The product shall be installed and serviced by a qualified person.
- 2.This product is non-waterproof. Please avoid the sun and rain. When installed outdoors please ensure it is mounted in a water proof enclosure.
- 3.Good heat dissipation will prolong the working life of the controller. Please ensure good ventilation.
- 4.Please check if the output voltage and current of any LED power supplies used comply with the requirement of the product.
- 5.Please ensure that adequate sized cable is used from the controller to the LED lights to carry the current. Please also ensure that the cable is secured tightly in the connector.
- 6.For safety consideration, PVC or rubber cord of 0.75-1.5mm² is recommended for input and output terminal(s) . Flat power cord is not suitable. Ensure all wire connections and polarities are correct before applying power to avoid any damages to the LED lights.
- 7.If a fault occurs please return the product to your supplier. Do not attempt to fix this product by yourself.

※ The contents of this manual are updated without prior notice. If the function of the product you are using is inconsistent with the instructions, the function of the product shall prevail. Please contact us if you have any questions .

EUP45T-1WMC-0

概述

EUP45T-1WMC-0 是一款可以提供 500/700/900/1050mA 四档电流的 LED 驱动器。这款驱动器支持前沿切相和后沿切相调光器，可以与兼容多品牌系统(飞利浦, ABB, 路创, 西门子, 西蒙, 松下等)配合使用, 实现平滑调光的效果。



产品特点

- 单通道恒流输出, 多级电流可选
- 支持前沿/后沿切相调光
- 调光电压范围: 40-240VAC
- 高效率达: 87%
- 调光曲线平滑, 无闪烁
- 输出短路保护; 过流保护
- 适用室内 LED 灯具, 比如筒灯, 面板灯等


应用




技术参数

型号	EUP45T-1WMC-0																																	
输入	效率	87%@230VAC, 满载																																
	电压	200VAC-240VAC																																
	频率	50/60Hz																																
	功率因素	>0.5@230VAC, 满载																																
	电流	0.4Amax@230VAC, 满载																																
	调光电压范围	40-240VAC																																
	浪涌电流	20A@230VAC																																
输出	电流/电压/功率	500mA/33-65VDC/32.5W 900mA/33-50VDC/45W 700mA/33-65VDC/45.5W 1050mA/33-42VDC/44.1W																																
	波纹电流	<3%																																
	通道	1																																
	电流精度	±7%																																
	空载输出电压	84V Max																																
	启动延时	<1s, at230Vac																																
<table border="1" style="margin-left: auto; margin-right: auto;"> <caption>电流选择表</caption> <tr> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> <td><input type="checkbox"/></td> </tr> <tr> <td>ON</td> <td>OFF</td> <td>1</td> <td>2</td> <td>3</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>500mA</td> <td>700mA</td> <td>900mA</td> <td>1050mA</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>33-65V</td> <td>33-65V</td> <td>33-50V</td> <td>33-42V</td> <td></td> <td></td> </tr> </table> <p>备注: 出厂默认设置电流为500mA(1,2,3在OFF状态)</p>			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	ON	OFF	1	2	3						500mA	700mA	900mA	1050mA					33-65V	33-65V	33-50V	33-42V		
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>																											
ON	OFF	1	2	3																														
		500mA	700mA	900mA	1050mA																													
		33-65V	33-65V	33-50V	33-42V																													
功能	调光方式	前沿 后沿切相调光																																
保护	短路	打嗝, 去除故障后自恢复																																
	过流	打嗝, 故障排除后自恢复																																
其它	工作温度	-20°C~40°C																																
	储存温度、湿度	-40°C~85°C, 20-90%RH																																
	tc	90°C																																
	材质	PC																																
	防水等级	IP20																																
	寿命	30,000小时@tc:90°C																																
	质保	3年																																
	开关周期	>15,000次																																
	包装重量	净重: 225g±5%/个; 50个/箱; 11.75kg±5%/箱; 外箱尺寸: 516*337*179mm(L*W*H)																																
尺寸	137*82*31mm(长*宽*高)																																	


产品尺寸




应用接线图




调光曲线



降额曲线



Eff. vs 负载



注意事项

1. 本产品请由具有专业资格的人员进行调试安装。
2. 本产品不能防水，需避免日晒雨淋，如安装在户外，请用防水箱。
3. 良好的散热条件会延长产品的使用寿命，请把产品安装在通风良好的环境。
4. 请检查使用的LED电源输出电压电流，是否符合产品要求。
5. 出于安全考虑，推荐输入和输出(信号端除外)用0.75-1.5mm²PVC或橡胶线缆，并确保接线牢固，以免电线过热或接触不良触发事故。扁平电源线不适用。
6. 通电调试前，应确保所有接线正确，以避免因接线错误而导致灯具损坏。
7. 如果发生故障，请勿私自维修；如有疑问，请联系供应商。

※ 本说明书内容如有更新，恕不另行通知。若您使用的产品功能与说明书不一致时，请以产品为准。如有疑问请与我们联系。